



可选配件 | OPTIONAL



名称：防静电垫  
材质：φ1.6多股软铜丝绳  
用途：高空安装时的防静电安全装置



名称：遮光板  
材质：铝合金  
用途：单侧防眩光遮光

详细参数 | DETAILED PARAMETERS

规格	产品型号	额定功率	光源数量	输入电压	控制方式	灰阶	角度区间	光通量	光源种类
单色常亮	TGSA-S1-50W	50W	1.3W*36PCS	AC220V	OFF/ON	—	6°-60°	4250LM	SMD3030
	TGSA-S2-80W	80W	1.3W*72PCS	AC220V	OFF/ON	—	6°-60°	7200LM	SMD3030
	TGSA-S2-100W	100W	1.3W*72PCS	AC220V	OFF/ON	—	6°-60°	8500LM	SMD3030
	TGSA-M3-120W	120W	1.3W*108PCS	AC220V	OFF/ON	—	6°-60°	10800LM	SMD3030
	TGSA-M3-150W	150W	1.3W*108PCS	AC220V	OFF/ON	—	6°-60°	12750LM	SMD3030
	TGSA-L4-200W	200W	1.3W*144PCS	AC220V	OFF/ON	—	6°-60°	17000LM	SMD3030
单色外控	TGSA-S1-D50W	50W	1.3W*36PCS	AC220V	DMX512	65536	6°-60°	4250LM	SMD3030
	TGSA-S2-D100W	100W	1.3W*72PCS	AC220V	DMX512	65536	6°-60°	8500LM	SMD3030
	TGSA-M3-D150W	150W	1.3W*108PCS	AC220V	DMX512	65536	6°-60°	12750LM	SMD3030
	TGSA-L4-D200W	200W	1.3W*144PCS	AC220V	DMX512	65536	6°-60°	17000LM	SMD3030
RGB外控	TGSA-S1-RGB50W	50W	1.3W*36PCS	AC220V	DMX512	65536	15°-60°	—	SMD5050 3in1
	TGSA-S2-RGB100W	100W	1.3W*72PCS	AC220V	DMX512	65536	15°-60°	—	SMD5050 3in1
	TGSA-M3-RGB150W	150W	1.3W*108PCS	AC220V	DMX512	65536	15°-60°	—	SMD5050 3in1
	TGSA-L4-RGB200W	200W	1.3W*144PCS	AC220V	DMX512	65536	15°-60°	—	SMD5050 3in1
RGBW外控	TGSA-S1-RGBW80W	54W+24W	8W*12PCS	AC220V	DMX512	65536	10°-60°	—	SMD5050 4in1
	TGSA-S2-RGBW150W	108W+48W	8W*24PCS	AC220V	DMX512	65536	10°-60°	—	SMD5050 4in1
	TGSA-M3-RGBW230W	160W+72W	8W*36PCS	AC220V	DMX512	65536	10°-60°	—	SMD5050 4in1
	TGSA-L4-RGBW310W	210W+100W	8W*48PCS	AC220V	DMX512	65536	10°-60°	—	SMD5050 4in1

备注：①光通量基于4000K色温 ②以上角度全指半角

