

Class C Backlit Panel Light

AC
220-240V

CRI ≥ 80

RoHS

CE

PF ≥ 0.9

SDCM
< 6

ERP



Benefits

- Up to 160lm/w for whole fixture.
- Ultra-thin, products size only 28mm.

Item No.	Voltage	Wattage	Lumen	Efficiency	CRI	PF	Dimmable	CCT(K)	Driver	Material	Dimension	IP
HBL01-2220	220~240V	21.25W	3400LM	160LM/W	80	>0.9	NO	3000K/4000K/6500K	External	AL+SPCC+PS	595×595×28mm	IP20
HBL01-2220-CCT	220~240V	21.25W	3400LM	160LM/W	80	>0.9	NO	3000K-4000K-6500K	External	AL+SPCC+PS	595×595×28mm	IP20
HBL01-2220U	220~240V	21.25W	3400LM	160LM/W	80	>0.9	NO	3000K/4000K/6500K	External	AL+SPCC+PS	595×595×28mm	IP20
HBL01-1420	220~240V	21.25W	3400LM	160LM/W	80	>0.9	NO	3000K/4000K/6500K	External	AL+SPCC+PS	295×1195×28mm	IP20
HBL01-1420-CCT	220~240V	21.25W	3400LM	160LM/W	80	>0.9	NO	3000K-4000K-6500K	External	AL+SPCC+PS	295×1195×28mm	IP20
HBL01-1420U	220~240V	21.25W	3400LM	160LM/W	80	>0.9	NO	3000K/4000K/6500K	External	AL+SPCC+PS	295×1195×28mm	IP20

